

Technical Description

GAS CYLINDER CONTAINER SGL+

- CONSTRUCTION**
- 4 jack rings for comfortable transportation
 - Metal runners for fork-lift transport and ground ventilation
 - Holding brackets and straps protect the gas cylinders from falling over
 - Best-Point-Technology (joining process, the protective zinc coating is not damaged)

- MATERIAL**
- Galvanized sheet steel S220 GD Z; 1.0241 and S250 GD Z; 1.0242
 - Surface: MB, hot-dip galvanized
 - Trapezoidal sheet thickness: 0.8mm
 - Profile thickness: 1.5mm or 2mm

- FLOOR**
- Press gratings are characterized by high torsional rigidity and stability
 - Thickness: 20mm
 - Load bearing capacity: 500kg/m² (permissible area load)
 - Material according to DIN EN 10025: S235 JR (ST 37-2)
 - Surface: hot-dip galvanized

- CRANE HANDLING**
- Can be lifted by crane when empty

SIZE/WEIGHT

SGL+	1.5x1.5	1x2	2x2	3x2	4x2
Width external/internal (mm)	1500/1375	2100/1975	2100/1975	2100/1975	2100/1975
Length external/internal (mm)	1500/1375	1100/975	2100/1975	3100/2975	4100/3975
Height external/internal (mm)	2100/1935	2100/1935	2100/1935	2100/1935	2100/1935
Weight (incl. accessories) (kg)	240	240	350	500	650

- DOORS**
- SGL+1.5x1.5: SE (in front face, single door), 1305 x 1890mm (clearance dimensions: 1308 x 1855mm)
 - SGL+1x2: SZ (in front face, double door), 1750 x 1890mm (clearance dimensions: 1758 x 1855mm)
 - SGL+2x2: SZ (in front face, double door), 1750 x 1890mm (clearance dimensions: 1758 x 1855mm)
 - SGL+3x2: LE/LE (2x in side wall, single door), 1305 x 1890mm (clearance dimensions: 1308 x 1855mm)
 - SGL+4x2: LZ/LZ (2x in side wall, double door), 1750 x 1890mm (clearance dimensions: 1758 x 1855mm)
 - Entrance height: approx. 120mm
 - With mortise lock (according to DIN 18251-1) and profile cylinder (PZ 25/25), including 3 keys
 - Short plate and door handle pair in aluminium

- DELIVERY**
- Assembled delivery